

10 Watt Easy-Fit Fluorescent Range



The Bardic 10W Easy-Fit range of exit and emergency lights is modular and completely user friendly for the specifier and user alike.

Regardless of the diffuser type or configuration the body remains the same.

Features

- Choice of wall or ceiling mounting
- Choice of exit or emergency lighting diffusers
- Designed and tested to comply with AS/NZS 2293
- Automatic battery low voltage cut-out to prevent overdischarge of the battery.
- Snap-fit diffuser design
- Easy to install and remove for maintenance purposes
- Available with Sealed Lead Acid batteries
 - Nickel Cadmium batteries
 - Nickel Metal Hydrate batteries
- Glass filled polycarbonate body which has high U.V-stability and a flammability rating of V-0
- Red L.E.D. indicates a healthy A.C. mains supply and functioning charger
- Test switch to test the emergency operation while A.C. mains is healthy
- Internal switch link in M and S models to permit connection of an external switch to control the mains operated lamp without affecting the emergency operation.

MH
POWER SYSTEMS

BARDIC
emergency lighting

10 WATT EASY-FIT FLUORESCENT SPECIFICATION



AUSTRALIA
Head Office
 9 Mosrael Place
 Rowville Victoria 3178
 Telephone: (61 3) 9763 0555
 Facsimile: 1300 733 005

New South Wales
 Unit 21/14 Stanton Road
 Seven Hills NSW 2147
 Telephone: (61 2) 9674 3187
 Facsimile: 1300 733 005

Queensland
 12 The Corso
 Seven Hills QLD 4170
 Telephone: (61 7) 3902 0902
 Facsimile: 1300 733 005

South Australia
 89A Grange Road
 Allenby Gardens SA 5009
 Telephone: (61 8) 8340 4081
 Facsimile: 1300 733 005

Western Australia
 B-Type Agencies Pty Ltd
 Unit 2/15 Narloo Street
 Malaga WA 6090 Perth
 Telephone: (61 8) 9209 2220
 Facsimile: (61 8) 9209 2229
 Email: Infor@btype.com.au

NEW ZEALAND
Auckland
 Unit B 237 Bush Road
 Albany, Auckland
 Telephone: (649) 415 6615
 Facsimile: (649) 415 8160

Wellington
 Unit 7 30-32 Downer Street
 Lower Hutt, Wellington
 Telephone: (644) 586 6188
 Facsimile: (644) 586 6088

Christchurch
 8 Kirkdale Place
 Avonhead, Christchurch
 Telephone: (643) 358 8444
 Facsimile: (643) 358 8446

		SELF CONTAINED LUMINAIRES						NEW DIFFUSERS (with peel off arrows)		
		M10S	M10NS	NM10S	NM10NS	S10S	S10NS	XPO	CM1	CM2
Function		Maintained 10W	Maintained 10W	Non Maint. 10W	Non Maint. 10W	Sustained 10W	Sustained 10W			
Battery		Lead Acid	High Temp Nicad	Lead Acid Nicad	High temp	Lead Acid Nicad	High temp			
Emergency duration after a 16 hour recharge on commissioning		2 Hour Minimum	2 Hour Minimum	2 Hour Minimum	2 Hour Minimum	2 Hour Minimum	2 Hour Minimum			
Power Consumption (Maximum)		14VA	14VA	10VA	10VA	14VA	14VA			
Input Voltage		240VAC								
Frequency		50 Hz								
Environment		Indoor								
Standards		AS/NZS 2293								
Body Construction		Glass filled Polycarbonate								
Backplate Construction		Sheet Steel – White								
Diffuser Construction		Acrylic								
IP Classification		IP21								
Charger		Constant Voltage				Constant Voltage	Constant Voltage			
Sentinel Compatible		Yes		Yes		Yes				
Weight		3kg	2kg	3kg		3kg				
Length	386mm									
Width	155mm									
Depth – Over ceiling Exit Diffuser	218mm									
– Over ceiling/wall Opal Diffuser	110mm									
– Over Wall Exit Diffuser	120mm									
								DIFFUSER WITH BODY		